

## SD-TEMP-xx Sensor

### Self-Describing Air/Water/Soil Temperature Sensor

For use with HOBO MX1104 and MX1105 multi-channel data loggers, this air/water/soil temperature sensor offers integrated strain relief, so the probe is secured to the logger. And it features Self-Describing technology to automatically communicate configuration information to the logger, without any programming or extensive user setup.

#### Supported Measurements:

Air Temperature, Soil Temperature, Temperature and Water Temperature

#### Key Advantages:

- Self-Describing technology for quick, easy setup
- Locking jack to ensure sensor is connected and stays connected
- Measurement range of -40° and 100°C (-40° to 212°F)
- Accuracy of  $\pm 0.15^{\circ}\text{C}$  from 0° to 70°C ( $\pm 0.27^{\circ}\text{F}$  from 32° to 158°F)
- Available in lengths of 0.3 m (1 ft), 1.8 m (6 ft), 6.1 m, (20 ft) & 15.2 m (50 ft)



## SD-TEMP-xx Sensor Specifications

Measurement Range	-40° to 50°C (-40° to 122°F) in water; -40° to 100°C (-40° to 212°F) in air
Accuracy	±0.15°C from 0° to 50°C (±0.27°F from 32° to 122°F), insert probe 2.3 cm (0.9 inches) minimum; see Plot A
Resolution	0.002° at 25°C (0.003° at 77°F)
Drift	<0.1°C (<0.2°F) per year
Response Time in Air	2 minutes typical to 90% in air moving 1 m/s (2.2 mph)
Response Time in Stirred Water	30 seconds typical to 90%
Operating Range	Sensor tip and cable immersion in fresh water up to 50°C (122°F) for 1 year
Probe Housing	Copper-plated sensor tip
Probe Dimensions	5.1 x 33 mm (0.2 x 1.3 inches)
Cable Length	SD-TEMP-01: 0.3 m (1 ft) SD-TEMP-06: 1.8 m (6 ft) SD-TEMP-20: 5.1 m (20 ft) SD-TEMP-50: 15.2 m (50 ft)

## Contact Us

**HOB0**®

Data Logging Solutions  
Australia - New Zealand

**OneTemp**<sup>o</sup>pty Ltd  
MEASURE | CONTROL | RECORD

Australia: 1300 186 107 | [sales@hobodataloggers.com.au](mailto:sales@hobodataloggers.com.au)  
New Zealand: 0800 104 904 | [sales@onetemp.co.nz](mailto:sales@onetemp.co.nz)