

Insertion Temperature Sensor

Featuring LoRaWAN®

TS101

Milesight



Milesight TS101 is an all-in-one insertion temperature sensor with an integrated transmitter. It is equipped with an advanced measuring unit that provides a wide temperature measuring range.

With IP67 and IK10 ratings, the exquisite TS101 sensor is suitable for monitoring the inner temperature of Tobacco or grain stacks. It can also be applied in other warehousing scenarios which require inner temperature detection with high efficiency.

TS101 is compatible with Milesight LoRaWAN® gateway and mainstream LoRaWAN® network servers. With this low power consumption technology, TS101 can work for up to 10 years with a 4,000mAh battery. Combining with Milesight LoRaWAN® gateway and Milesight IoT Cloud solution, users can manage all sensor data remotely and visually.

◆ Features

- Equipped with highly accurate and stable DS18B20 temperature sensor chip with high resolution
- Adopt food-grade stainless-steel probe and shell material for efficient and safe detection
- Store up to 1200 sets of data locally and support data retrievability and retransmission
- IP67 and IK10 rated and phosphine corrosion-resistant for harsh environment
- Built-in 4000 mAh replaceable battery and works for up to 10 years without replacement
- Integrated and compact design for wireless deployment

- Built-in NFC for easy configuration
- Compatible with standard LoRaWAN® gateways and network servers
- Quick and easy management with Milesight IoT Cloud solution

◆ Specifications

| Wireless Transmission | |
|---------------------------------|--|
| Protocol | LoRaWAN® |
| Frequency | CN470/IN865/RU864/EU868/US915/AU915/KR920/AS923-1&2&3&4 |
| Tx Power | 16 dBm (868 MHz)/20 dBm (915 MHz)/19 dBm (470 MHz) |
| Sensitivity | -137 dBm @300bps |
| Mode | OTAA/ABP Class A |
| Measurement | |
| Detecting Range | -30°C ~ +70°C |
| Accuracy | ± 0.5°C |
| Resolution | 0.1°C |
| Operation | |
| Power On & Off | NFC, Power Button (Internal) |
| Configuration | NFC Configuration via Mobile App |
| Advanced Feature | Data Storage, Data Retransmission, Data Retrievability, Abrupt Temperature Change Alarm |
| Physical Characteristics | |
| Power Supply | 1 × 4000 mAh ER18505 Li-SOCl ₂ Replaceable Battery |
| Battery Life* | 10 Years (1 Hour Report Interval, 25°C) |
| Operating Temperature | -30°C ~ +70°C |
| Relative Humidity | 0 ~ 95% (Non-condensing) |
| Material & Color | Transceiver: ABS+PC(Food-Grade, Phosphine Corrosion resistant), White Sensor Probe: 316 Stainless Steel (Food-Grade, Phosphine Corrosion Resistant) , Silver Grey |
| Ingress Protection | IP67 |
| Impact Protection | IK10 (Transceiver) |
| Dimension | Transceiver: Φ 92 × 92 × 26 mm (Φ 3.62 × 3.62 × 1.02 in) Sensor Probe: Φ 7 × 400 mm (Φ 0.28 × 15.75 in) |
| Installation | Insert Installation |

* Tested under laboratory conditions and for guideline purposes only.

◆ Dimensions(mm)

