



DATA SHEET

Accessories


For transmitters and transmitter probes




ACCESSORIES FOR PRESSURE TRANSMITTERS

Junctions


Designation: J.D.C
Sales reference: 11921



Designation: J.T.C
Sales reference: 11922



Designation: J.Y.C
Sales reference: 11923



Pressure connections

Designation: KR 483
Sales reference: 11438



Designation: DP 339
Sales reference: 11090



Designation: 482
Sales reference: 10221



Designation: 483
Sales reference: 10222



Designation: DP 447 (10388)
Sales reference: 10388










Designation: KR 447 (13015)
Sales reference: 13015



Designation: PC 482 (several sale references according to the length)



Connection tubes

Designation	Sales reference	Description	Illustration
C-58-1	10325	1 m of clear cristal tube, Ø 5 x 8 mm	
C-58-25	10321	25 m of clear cristal tube, Ø 5 x 8 mm	
C-58-50	14207	50 m of clear cristal tube, Ø 5 x 8 mm	
SB-47-1	15088	1 m of white silicone tube, Ø 4 x 7 mm	
SB-47-25	15089	25 m of white silicone tube, Ø 4 x 7 mm	
SN-47-1	10327	1 m of black silicone tube, Ø 4 x 7 mm	
SN-47-25	12761	25 m of black silicone tube, Ø 4 x 7 mm	

ACCESSORIES FOR HUMIDITY TRANSMITTERS


Protection caps for humidity probes

Designation (Sales reference)	 EPP2 (13799)	 EPI25 (13800)	 EPI100 (13801)	 EPFI (13797)	 EPFT (13798)	 EPH202 (23667)
Features	Cap: ABS ⁽¹⁾ Filter: meshed, 316L st. steel 30 mm length	Cap: 316 stainless steel Filter: meshed, 316L st. steel 30 mm length	Cap: 316L stainless steel Filter: meshed, 316L st. steel 30 mm length	Cap: 316L stainless steel Filter: sintered, 316L st. steel 30 mm length	Cap: PTFE ⁽²⁾ Filter: sintered, PTFE ⁽²⁾ 30 mm length	Cap: MnO ₂ ⁽³⁾ Filter: sintered, PTFE ⁽²⁾ 33 mm length
Max. particle	25 µm	25 µm	100 µm	25 µm	10 µm	50 µm
Max. air velocity	25 m/s	25 m/s	20 m/s	25 m/s	25 m/s	25 m/s
Max. temperature	80°C	180°C	180°C	180°C	180°C	180°C
Relative humidity	95% RH	95% RH	100% RH	90% RH	90% RH	95% RH


EXAMPLE OF APPLICATIONS

HVAC air-conditioning systems	✓	✓				
Cold storage rooms			✓		✓	
Industrial environment	✓	✓	✓	✓	✓	
Clean rooms in pharmaceutical/electronics industries	✓	✓	✓	✓	✓	✓
Drying processes				✓	✓	
Swimming pools					✓	

⁽¹⁾ABS: white acrylonitrile butadiene styrene / ⁽²⁾PTFE : white Polytetrafluoroethylene / ⁽³⁾MnO₂ : manganese dioxide / (4): PE : Polyethylene

Designation	Sales reference	Description	Illustration
CPH	13804	Bag of 10 waterproof protective caps for Ø 13 mm humidity probe	



Salt solutions

Designation	Sales reference	Description	Illustration
KSH-11	15644	11%HR saturated salt solution. For the verification of Ø 13 mm humidity probes.	
KSH-44	15645	44%HR saturated salt solution. For the verification of Ø 13 mm humidity probes.	
KSH-85	15646	85%HR saturated salt solution. For the verification of Ø 13 mm humidity probes.	

Accessories for installing our probes





Designation	Sales reference	Description	Illustration
RCT-13-12	13788	Sliding fitting in stainless steel 1/2 cylindrical gas with PTFE olive for probe Ø 13 mm.	
KI-DIN/RCCT-13/12	13790	Stainless steel clamp as per DIN 2566. With cylindrical 1/2 gas sliding connector, Ø 13 mm, PTFE ferrule. For Ø 13 mm probe.	
BFP-13	18401	Plastic mounting flange with cable gland for Ø 13 mm probe.	
BF-13	15747	Stainless steel mounting flange for Ø 13 mm probe.	
SFM-13	13795	Translucent polycarbonate wall-mount plate for Ø 13 mm probe.	
BF-8	27897	Stainless steel mounting bracket. Ø 8 mm. For hotwire probe Ø 8 mm (supplied alone - not mounted).	
RCT-8-12	27920	Supply and mounting of the stainless steel bicone fitting. RCT-8-12 on hotwire probe. With PTFE olive, 1/2 gas cylindrical thread, for hot wire probe Ø 8 mm (should be ordered together with the hot wire probe).	
KI-DIN/RCTFC-8/12	13812	Supply and mounting of the stainless steel threaded flange according to DIN 2566, type KI-DIN/RCTFC-8/12 on a hot wire probe Ø 8 mm. With PTFE olive, 1/2 gas cylindrical thread (should be ordered together with the hot wire probe).	
PF-110	24227	ABS wall-mount plate for stats and Class 110/210 transmitters.	
PF300	13825	Stainless steel wall-mount plate for Si-C320.	
Si-ACC-BPPM	28006	Si-ACC-BPPM Silicone mounting flange for Si-PRO-CO, Si-PRO-CO2 and Si-PRO-VOC probes.	
Si-ACC-WMB	28012	Si-ACC-WMB stainless steel wall bracket for Si-PRO-CO2, Si-PRO-CO and Si-PRO-VOC probes.	

Protection against events


Designation	Sales reference	Description	Illustration
PEM12-13	13805	Weather protection shield including 12 ring for outdoor mounting of Ø 13 mm humidity probe.	
Si-ACC-OS	28005	Protective shield for Si-C320 transmitters. It ensures the protection of transmitters against solar radiation and most of the precipitation when these are installed outdoors.	

ACCESSORIES FOR MULTIFUNCTION TRANSMITTERS AND FLUSHMOUNT MULTIFUNCTION TRANSMITTERS

Cable and extensions for interchangeable probes



Designation	Sales reference	Description	Illustration
Si-ACC-R2	27999	2 m probe cable for class 320 interchangeable probes.	
Si-ACC-RVP	28002	Si-ACC-RVP cable for connecting Si-PRO-V-300 and Si-PRO-U-W probes to class 320 sensors.	
Si-ACC-R5	28000	5 m extension for probe cable Si-ACC-R2.	
Si-ACC-R10	28001	10 m extension for probe cable Si-ACC-R2.	

SOFTWARE




Designation	Sales reference	Description	Illustration
LCC-S	24106	Configuration software for transmitters (only for class 110/210 and monostats). Supplied with USB interface.	
Si-ACC-USB-CC	27998	PC cable for configuration of the class 320 transmitters (software available for free from Sauer mann website).	

POWER SUPPLY

AC power supply

Designation	Sales reference	Description	Illustration
KI-AL-100-A	12964	Class 2 power supply. Mounting with integrated brackets. Input voltage: 230 V _{AC} . Output voltage 24 V _{AC} . Intensity 100 mA. For class 50/110 and Monostat.	
KI-AL-750-A	24709	Class 2 power supply. DIN rail mounting. Input voltage: 230 V _{AC} . Output voltage: 24 V _{AC} . Power 18 VA. Intensity 750 mA.	

DC power supply

Designation	Sales reference	Description	Illustration
KI-AL-100-C	14063	Class 2 stabilized power supply. Input voltage: 230 V _{AC} . Output voltage: 24 V _{DC} . Intensity: 250 mA. For class 50/110 and Monostat.	
KI-AL-CPA	14225	Class 2 stabilized power supply. Input voltage 230 V _{AC} . Output voltage 24 V _{CC} . Intensity 250 mA. Power: 6 VA.	
KI-AL-600-C	24695	Class 2 stabilized switch mode power supply. Rail DIN mouting. Input voltage: 110/240 V _{AC} . Output voltage: 24 V _{DC} . Power 15 W. Intensity 360 mA.	
KI-AL-1000-C	13973	Class 2 stabilized power supply. Mounting with integrated brackets. Input voltage: 230 V _{AC} . Output voltage: 24 V _{DC} . Power: 24 VA. Intensity: 1 A	

OTHER ACCESSORIES

Designation	Sales reference	Description	Illustration
Si-ACC-RAIL	28003	DIN rail mounting kit for Si-C320 transmitters.	

OneTemp^o
measure | control | record

1300 768 887
www.onetemp.com.au

sauermanngroup.com

