

JUMO

More than **sensors + automation**

JUMO DELOS S02

Precision pressure transmitter with switching contacts and display



The features at a glance

- Pressure transmitter for liquid and gaseous media
- High degree of process reliability due to maximum accuracy and long-term stability
- Easy configuration via Bluetooth/mobile phone app or IO-Link
- Ethernet-based version available
- Direct cloud connection possible



Type 405056



More than **sensors + automation**

Brief overview

The clever pressure transmitter is used to acquire relative and absolute pressure. It is suitable for numerous industries and applications. This device features precise measurement, flexible application possibilities, and absolute user-friendliness. The Ethernet version can reduce hardware costs and save time by transferring measurement data directly to the cloud.

Other advantages

- Any installation position can be set due to rotatable housing
- Continuous self-monitoring and feedback on operating status possible
- Optimal readability, configuration, and electrical installation available
- Maximum adaptability due to modular structure
- A wide range of measuring ranges and process connections can be applied

Technical data

Product name	JUMO DELOS S02
Type	405056
Measurement inputs	0.1 to 60 bar relative, 0.4 to 60 bar absolute
Measurement outputs (adjustable)	– 1 × PNP switching output and IO-Link – 1 × PNP switching output and 1 × analog output – 2 × PNP switching outputs – Ethernet SPE with PoDL (Modbus TCP slave)
Voltage supply	24 V DC
Approvals	cUL

OneTemp^o_{pty ltd}
measure | control | record
1300 768 887
www.onetemp.com.au

www.jumo.net

